

Kleanline® CWHO Series



Compact Hot Water Heaters - Oil Fired

Low Pressure Series: Replace inefficient, fuel wasting storage type water heaters with our compact, on-demand Kleanline® coil type heaters. Only when flow starts, cold water enters heating coil. 15 seconds later, it exits at temperatures up to 210 Degrees F (temperature rise depends on flow rate). As long as no water flows, no fuel is used. Perfect for milkhouses, farms, construction sites, slaughter houses, production lines - anywhere lots of low cost, hot water is needed from a small, high efficiency water heater.

High Pressure Series: With three firing rates to choose from, and operating pressures up to 3000 PSI, you can convert your cold pressure washer into a hot water machine simply by connecting your outlet hose to our heater unit. This high efficiency Kleanline® coil type water heater will automatically sense water flow and heat the water up to as high as 210 Degrees F (depending on the model and water flow). Simply plug heater into any 115 VAC plug outlet (max 5 amp draw) and enjoy the increased cleaning capability of hot water washing right away.

12 Volt DC Series: These models incorporate the new RW Beckett, 12 Volt DC, Power Oil Burners. Similar to the high pressure series, units described can be connected to any 12 Volt DC battery power source. This makes them the perfect add-on for truck mounted, gas engine driven, cold pressure washers.

Model	PSI	GPM	Electricals	HP	Dimensions (Inches)	Weight
CWHO140	3000	6.0	115/60/1.5 Amp	1/5	26 L x 20 W x 34 H	185 lbs.
CWHOL140	125	6.0	115/60/1.5 Amp	1/5	26 L x 20 W x 42 H	210 lbs.
CWHO210	3000	8.0	115/60/1.5 Amp	1/5	26 L x 20 W x 34 H	190 lbs.
CWHOL210	125	8.0	115/60/1.5 Amp	1/5	26 L x 20 W x 42H	215 lbs.
CWHO300	3000	10.0	115/60/1.5 Amp	1/5	26 L x 20 W x 34 H	195 lbs.
CWHOL300	125	10.0	115/60/1.5 Amp	1/5	26 L x 20 W x 42 H	220 lbs.
CWHO140-12	3000	6.0	12 VDC, 16 Amp	1/6	26 L x 20 W x 34 H	185 lbs.
CWHO210-12	3000	8.0	12 VDC, 16 Amp	1/6	26 L x 20 W x 34 H	190 lbs.
CWHO300-12	3000	10.0	12 VDC, 16 Amp	1/6	26 L x 20 W x 34 H	195 lbs.

Standard On All Models:

- ◆ Compact Design - Saves Space
- ◆ Beckett Power Oil Burner with Flame Lock
- ◆ Efficient "On Demand Only" Operation
- ◆ Flow Switch Controlled
- ◆ Adjustable Temperature Control
- ◆ Flame Safety Relay ("L" Models)
- ◆ Up to 10 GPM Flow Rate
- ◆ Clean Burning Kerosene or Fuel Oil
- ◆ Schedule 80, Heavy Wall Steel Heating Coil
- ◆ Insulated Construction
- ◆ Pressure and Temperature Relief Valve
- ◆ Compact Size - Big Heating Capacity

Options Available:

- ◆ GFCI Safety Cord - 12' (115 Volt Models)
- ◆ Fuel Tank, Various Sizes Available
- ◆ Stainless Steel Coil Wrap - Stainless Coils
- ◆ Circulation and Booster Pumps

Custom Designs: Call For Any Application From 0-200 GPM and From 0-6000 PSI, Hot or Cold



Custom Klean Corp.
 8890 Boak Road
 Holland Patent, NY 13354
 (315) 865-8101
www.kleanline.com

© 2003 Custom Klean Corp.
 Form #CWHG2003

Distributed By: