Kleanline® KCP Series



Portable Cold Pressure Washers, Gas Engine

These heavy duty Kleanline®, Gas Engine Driven, Cold Pressure Washers feature rugged rebuildable pumps with brass pressure manifolds (not aluminum). HD commercial engines mean many years of service.

- ♦ Reliable Honda Long Run Engines
- ♦ Triplex, Oil Bath, Comet Pump with Brass Pressure Manifold
- Pressure Safety Relief Valve Thermal Pump Protector
- Quick Coupled Soap Injector Sprays Soap at Low Pressure
- ◆ Trigger Wash Gun, Variable Pressure and Angle Nozzle
- ♦ 3/8" x 30', Steel Reinforced, Non-Marking, Pressure Hose
- ♦ Garden Hose Quick Coupler and Inlet Water Screen
- ♦ Easy Portability on 10" Ball Bearing Pneumatic Wheels

Model	PSI	GPM	Engine **	H.P.	Pump ***	L x W x H (Inches)	Weight
KCPH2424GEH	2400	2.4	Honda, RS, GC	5.0	Comet, Triplex, ABH	32 x 22 x 25	75 lbs.
KCPH2424GEHM *	2400	2.4	Honda, RS, GC	5.0	Comet, Triplex, ABH	32 x 22 x 25	80 lbs.
KCPI2503GEHSS	2500	3.0	Honda, RS, GX, CI	6.5	Comet, Triplex, CS	35 x 21 x 38	90 lbs.
KCPI3003GEH	3000	3.0	Honda, RS, GX, CI	9.0	Comet, Triplex, CS	35 x 21 x 38	130 lbs.
KCPI3004GEH	3000	4.0	Honda, RS, GX, CI	11.0	Comet, Triplex, CS	35 x 21 x 38	145 lbs.
KCPI4004GEHSS	4000	4.0	Honda, RS, GX, CI	13.0	Comet, Triplex, CS	35 x 21 x 38	145 lbs.
KCPI1502E	1500	2.0	Elec. Motor 115/60/1	2.0	Comet, Triplex, CS	30 x 18 x 24	75 lbs.

^{*} With Soap Tank

Industrial Gas Engine Cold Pressure Washer

Kleanline® industrial series cold pressure washers offer the toughest, hard working components, designed for continuous duty job requirements. Honda GX series, OHV engines and Comet/General triplex, crankshaft, ceramic plunger pumps will run and run. All are easily maintained and serviced.

- ♦ Premium Honda Engine with OHV, Low Oil Shutdown
- ♦ Ceramic Plunger, Crankshaft Style Triplex Pump
- ♦ Quad Unloader with Safety Relief Valve, Thermal Protector
- ◆ Trigger Gun, Quick Coupler Spray Tips
- Quick Connect Detergent Injector for Low Spray Soap Application
- ♦ 3/8" x 30', Steel Braid Wash Hose
- ♦ Easy Portability on 10" Ball Bearing Pneumatic Wheels
- ♦ Safety Roll Cage on IR Models Protects Components



Custom Klean Corp. 8890 Boak Road Holland Patent, NY 13354 (315) 865-8101 www.kleanline.com

© 2003 Custom Klean Corp. Form # KCP2003-A



Distributed By:

^{**} RS = Recoil Start, LO = Low Oil Protection, CI = Cast Iron Cylinder, OHV = Overhead Valve

^{***} ABH = Axial with Brass Pressure Head, CS = Crankshaft with Oil Bath