

# Kleanline® KS Series

## Two Pass, Hot Combinations, Oil Fired

The Kleanline® KS Series is for the operator who wants all the bells and whistles built in. This top of the line series is offered two ways - on four full pneumatic wheels or on a two pneumatic wheel/ two full swivel locking castor frame design - the choice is yours. It's powerhouse performance is available in hot high pressure water blasting or, with a quick change of the control, in 305 Deg. F superheated steam cleaning modes. The schedule 80, dual pass, .840" OD heating coil heats the water twice as hot because it heats both sides of the pipe at the same time. Each component throughout is the sturdiest we can find. From the stainless water tank, to the EZ-Tite™ slide base belt adjustment assembly, to the load handling motor controller, this machine is built to last. KS Signature Series owners of 15 years plus tell us this is the only machine they would ever want to own.



Model	PSI	GPM	Electricals	H.P.	Dimensions (Inches)	Weight
KS1603C	PW 1600 ST 350	PW 2.8 ST 1.5	230/60/1, 15 Amp	3.0	43 L x 33 W x 32 H	350 lbs.
KS2004C	PW 2000 ST 450	PW 3.6 ST 1.5	230/60/1, 24 Amp	5.0	43 L x 33 W x 32 H	395 lbs.
KS3004C	PW 3000 ST 450	PW 3.6 ST 1.5	230/60/1, 36 Amp	7.5	43 L x 33 W x 32 H	445 lbs.

### Standard On All Models:

- ◆ Oil Fired Burner with Auto Ignition Control
- ◆ .840" O.D., Schedule 80 Dual Pass, High Efficiency Coil
- ◆ Insulated, Horizontal, 100% Water Wall Firing Chamber
- ◆ Triplex, Ceramic Plunger, Oil Bath Pump
- ◆ Slow Pump Speed Extends Pump Life
- ◆ Durable Duplex Belt Drive with EZ-Tite™ Belt Adjust
- ◆ Stainless Water Tank with Inlet Filtration System
- ◆ HD Motor Controller, Low Amp Control Circuit
- ◆ Adj. Thermostat, Water Temps From 80 - 305 Deg. F
- ◆ Low Flow Safety Switch, No Flow Burner Control
- ◆ Thermal Relief Valve, Pressure Relief Valve
- ◆ Full PSI Adj., One Knob Change from PW to Steam
- ◆ Large 9 Gallon Kerosene or Diesel Fuel Tank
- ◆ Easy Maintenance Access Under Full Hinged Hood
- ◆ 3/8" x 50' Steel Wire Combo Hose, Insul. Trigger Gun
- ◆ Rugged Design, Built to Last, With All The Features

### Options Available:

- ◆ 208/60/1 Supply Voltage
- ◆ Ground Fault Interrupter Protection
- ◆ Variable Temperature Control
- ◆ 60 Second Auto-Stop™ Safety Feature
- ◆ Auto Start-Stop™ Remote Control
- ◆ Stainless Steel Machinery Cover
- ◆ Downstream Chemical Injection
- ◆ Magnetic or Chemical Hard Water Coil Protection
- ◆ 360 Deg. Swivel Hose Reel with Quick Coupler
- ◆ Four Full Pneumatic 10" Wheels

**Custom Designs: Call For Any Application From 0-200 GPM and From 0-6000 PSI, Hot or Cold**



**Custom Klean Corp.**  
 8890 Boak Road  
 Holland Patent, NY 13354  
 (315) 865-8101  
[www.kleanline.com](http://www.kleanline.com)

© 2003 Custom Klean Corp.  
 Form # KS2003

*Distributed By:*

