

Kleanline® KVC Series



Vertical, Hot Pressure Washers, Oil Fired

The Kleanline® KVC Series is designed around three key principles; rugged durability, easy maintenance and safety of operation. Tough brass head industrial pumps and 115% duty cycle motors are bolted down to sturdy steel frames. Our high efficiency, schedule 80 heating coil completely surrounds the burner flame to absorb the most heat and to eliminate combustion chamber burnout. The machine tips back for burner service, the fuel filter is "out there" so you can reach it and the pumping module is on top for easy access. Safety interlocking of the pump and burner switches, along with redundant temperature, pressure and flow controls produces one of the most inherently safe machines on the market today. These rugged performers are compact, highly maneuverable and built "bulldozer tough". Rated best value for your dollar, choose the model which is right for your cleaning needs.

Model	PSI	GPM	Electricals	H.P.	Dimensions (Inches)	Weight
KVC1022	1000	2.2	115/60/1, 17 Amp	1.5	32 L x 27 W x 36 H	300 lbs.
KVC1502	1500	2.0	115/60/1, 19 Amp	2.0	32 L x 27 W x 36 H	300 lbs.
KVC1103	1050	2.8	115/60/1, 19 Amp	2.0	32 L x 27 W x 36 H	300 lbs.
KVC1603	1600	2.8	230/60/1, 15 Amp	3.0	32 L x 27 W x 36 H	300 lbs.
KVC2004	2000	3.6	230/60/1, 24 Amp	5.0	32 L x 27 W x 36 H	335 lbs.
KVC3003	3000	2.4	230/60/1, 24 Amp	5.0	32 L x 27 W x 36 H	335 lbs.

Standard On All Models:

- ◆ Oil Fired, Power Burner with Auto Ignition Control
- ◆ .840" O.D., Schedule 80 Heating Coil for Long Life
- ◆ Insulated, Vertical, 100% Water Wall Firing Chamber
- ◆ Triplex, Ceramic Plunger, Oil Bath Pump
- ◆ Slow Pump Speed Extends Pump Life
- ◆ Durable Duplex Belt Drive on 230 Volt Models
- ◆ E-Z Tite™ Belt Adjustment - Takes 5 Seconds
- ◆ Watertite Control Box with H.D. Interlocked Switches
- ◆ Durable Brass Pressure Unloader Valve
- ◆ Temperature Relief Valve, Pressure Relief Valve
- ◆ Temperature Limit Switch, Pressure Limit Switch
- ◆ Upstream Metered Chemical Injection
- ◆ Rust Proof 9 Gal. Fuel Tank, Oversize Filter System
- ◆ Easy Maneuverability on Four 12" Pneumatic Wheels
- ◆ Rugged Construction, Designed for Easy Maintenance
- ◆ 3/8" x 50' Steel Wire Wash Hose, Insul. Trigger Gun

Options Available:

- ◆ 208/60/1 Supply Voltage
- ◆ Ground Fault Interrupter Protection
- ◆ Variable Temperature Control
- ◆ 60 Second Auto-Stop™ Safety Feature
- ◆ Auto Start-Stop™ Remote Control
- ◆ Stainless Steel Coil Wrap
- ◆ Heavy Duty Wrap Around Roll Cage
- ◆ One Gallon Chemical Holder
- ◆ 360 Deg. Swivel Hose Reel with Quick Coupler
- ◆ Steam Combination Feature

Custom Designs: Call For Any Application From 0-200 GPM and From 0-6000 PSI, Hot or Cold



Custom Klean Corp.
 8890 Boak Road
 Holland Patent, NY 13354
 (315) 865-8101
www.kleanline.com

© 2003 Custom Klean Corp.
 Form # KVC2003

Distributed By:

